

Package: rmsMD (via r-universe)

October 9, 2026

Type Package

Title Output Results from 'rms' Models for Medical Journals

Version 1.0.1

Date 2025-11-09

Description Provides streamlined functions for summarising and visualising regression models fitted with the 'rms' package, in the preferred format for medical journals. The 'modelsummary_rms()' function produces concise summaries for linear, logistic, and Cox regression models, including automatic handling of models containing restricted cubic spline (RCS) terms. The resulting summary dataframe can be easily converted into publication-ready documents using the 'flextable' and 'officer' packages. The 'gg rmsMD()' function creates clear and customizable plots ('ggplot2' objects) to visualise RCS terms.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

URL <https://rmsmd.github.io/rmsMD/>

BugReports <https://github.com/rmsMD/rmsMD/issues/>

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Imports rms, ggplot2, rlang, cowplot

Suggests knitr, rmarkdown, devtools, officer, flextable, dplyr, testthat (>= 3.0.0), vdiff, Hmisc

VignetteBuilder knitr

Config/testthat/edition 3

Config/pak/sysreqs cmake make libicu-dev libuv1-dev

Repository <https://rmsmd.r-universe.dev>

Date/Publication 2025-11-11 12:27:42 UTC

RemoteUrl <https://github.com/rmsmd/rmsmd>
RemoteRef HEAD
RemoteSha 3bed75c7e7909478fe283c4e9c12a4519a877ef5

Contents

ggrmsMD	2
modelsummary_rms	4
simulated_rmsMD_data	5
Index	6

ggrmsMD	<i>Create plots for RCS variables from an rms model</i>
---------	---

Description

The ggrmsMD function processes the output from models fitted using the rms package and produces one or more ggplot2 objects visualising restricted cubic splines (RCS). The function detects RCS terms in the model and plots them all, with a suitable y-axis selected based on the model type. This outputs a list of plots, or a multi-panel figure using the combined argument. As outputs are ggplot objects they can easily be further customised by the user.

Usage

```
ggrmsMD(  
  modelfit,  
  data,  
  noeffline = TRUE,  
  shade_inferior = "none",  
  combined = TRUE,  
  ylab = NULL,  
  xlab = NULL,  
  titles = NULL,  
  ylim = NULL,  
  log_y = FALSE,  
  log_y_breaks = NULL,  
  xlims = NULL,  
  log_x_vars = NULL,  
  log_x_breaks = NULL,  
  lrm_prob = FALSE,  
  var = NULL,  
  np = 400,  
  ...  
)
```

Arguments

<code>modelfit</code>	A model object from <code>ols</code> , <code>lrm</code> , or <code>cph</code> (from the <code>rms</code> package).
<code>data</code>	The dataset used to fit the model.
<code>noeffline</code>	Logical. If <code>TRUE</code> (default), adds a horizontal dashed line at 1 for odds/hazard ratio plots.
<code>shade_inferior</code>	Character. Options are "none" (default), "higher", or "lower". Applies red/green shading above or below 1 on the y-axis to indicate worse/better outcomes.
<code>combined</code>	Logical. If <code>TRUE</code> , returns a single multi-panel plot using <code>cowplot::plot_grid()</code> .
<code>ylab</code>	Optional character. Override the default y-axis label.
<code>xlabs</code>	A named list of x-axis labels for each variable. E.g., <code>list(age = "Age (years)", bmi = "BMI (kg/m²")</code>
<code>titles</code>	A named list of plot titles for each variable.
<code>ylim</code>	Numeric vector (length 2). y-axis limits applied to all plots. E.g., <code>c(0.5, 2)</code> .
<code>log_y</code>	Logical. If <code>TRUE</code> , y-axis is log10-transformed.
<code>log_y_breaks</code>	Optional numeric vector specifying y-axis tick marks when <code>log_y = TRUE</code> . E.g., <code>c(0.25, 0.5, 1, 2, 4)</code> .
<code>xlims</code>	A named list of x-axis limits per variable. E.g., <code>list(age = c(20, 80))</code> .
<code>log_x_vars</code>	Character vector. Names of variables for which x-axis should be log10-transformed.
<code>log_x_breaks</code>	A named list specifying x-axis tick marks for variables with log10-transformed x-axis.
<code>lrm_prob</code>	Logical. If <code>TRUE</code> and model is <code>lrm</code> , plots predicted probabilities instead of odds ratios.
<code>var</code>	Character vector. Optional. Variables to plot. If <code>NULL</code> (default), all RCS variables in the model will be plotted.
<code>np</code>	Integer. Number of points used to predict spline curves. Default is 400. Consider increasing when using log-transformed x-axes.
<code>...</code>	Additional arguments passed to <code>cowplot::plot_grid()</code> when <code>combined = TRUE</code> .

Value

A `ggplot` object (if one variable is plotted), a list of `ggplot` objects (if multiple variables), or a single combined `cowplot` plot if `combined = TRUE`.

Examples

```
# For details examples and plots please see the provided vignettes
```

modelsummary_rms

Create model summary for rms models

Description

The `modelsummary_rms` function processes the output from models fitted using the `rms` package and generates a summarized dataframe of the results. This summary is tailored for publication in medical journals, presenting effect estimates, confidence intervals, and p-values.

Usage

```
modelsummary_rms(
  modelfit,
  combine_ci = TRUE,
  round_dp_coef = 3,
  round_dp_p = 3,
  rcs_overallp = TRUE,
  hide_rcs_coef = TRUE,
  exp_coef = NULL,
  fullmodel = FALSE,
  MI_lrt = FALSE
)
```

Arguments

<code>modelfit</code>	The output from an <code>rms</code> model.
<code>combine_ci</code>	If TRUE, combines the effect estimates and 95% confidence intervals into a single column. Default is TRUE.
<code>round_dp_coef</code>	Specifies the number of decimal places to display for the effect estimates. Default is 3.
<code>round_dp_p</code>	Specifies the number of decimal places to display for P values. Default is 3.
<code>rcs_overallp</code>	If TRUE, provides an overall P value for Restricted Cubic Spline (RCS) terms, sourced from <code>anova(modelfit)</code> . Automatically selects appropriate test (LR, F or Wald)
<code>hide_rcs_coef</code>	If TRUE, hides the individual coefficients for Restricted Cubic Spline (RCS) variables.
<code>exp_coef</code>	If TRUE, outputs the exponentiated coefficients (<code>exp(coef)</code>) as the effect estimates. Applicable only for model types other than <code>ols</code> , <code>lrm</code> , or <code>cph</code> . If NULL, no exponentiation is performed. Default is NULL.
<code>fullmodel</code>	If TRUE, includes all intermediate steps in the summary, allowing users to verify and compare with standard model outputs.
<code>MI_lrt</code>	If TRUE then overall p-values for RCS terms from models with multiple imputed data from <code>fit.mult.impute</code> will represent likelihood ratio chi-square tests from <code>rms::processMI()</code> , rather than Wald tests.

Value

Returns a dataframe of results. This can easily be outputted to word using packages such as flextable and officer.

Examples

```
# For detailed examples please see the provided vignettes
```

simulated_rmsMD_data	<i>Simulated Data for the Vignette</i>
----------------------	--

Description

Generates a synthetic dataset for testing and demonstration purposes in the rmsMD package.

Usage

```
simulated_rmsMD_data(type = c("complete_case", "missing_for_MI"))
```

Arguments

type	Character string; either "complete_case" (no missing data) or "missing_for_MI" (introduces 10% missing data in each predictor).
------	---

Value

A data frame with simulated variables: age, bmi, sex, smoking, majorcomplication, lengthstay, time, and event.

Index

ggrmsMD, [2](#)

modelsummary_rms, [4](#)

simulated_rmsMD_data, [5](#)